



## ECHO 3AC/24DC/5A



### Features

- 3-phase switch mode power supplies
- Wide temperature range -25 °C to 70 °C

- Output status signaling
- Slim design with metal chassis

### Technical Data

| Model                                                                        | WAT-0303-01                                                                     |
|------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Type                                                                         | E 3AC/24VDC/5A                                                                  |
| Input voltage                                                                | Rated : 3*400Vac-500Vac<br>Range : 3*320Vac-575Vac<br>(<360Vac Derating 0.5%/V) |
| Input frequency                                                              | 50/60Hz                                                                         |
| Input current                                                                | 0.5A @ 3X400Vac                                                                 |
| Standby power                                                                | <10W                                                                            |
| Power factor                                                                 | >0.5(400VAC)                                                                    |
| Inrush current                                                               | <20A                                                                            |
| Recommend fuse                                                               | 1A Character C circuit breaker                                                  |
| Efficiency (typ)                                                             | >88%                                                                            |
| Output voltage                                                               | 22-28Vdc(adjustable)                                                            |
| Output current                                                               | 5A                                                                              |
| Output power                                                                 | 120W                                                                            |
| Base Ripple                                                                  | <100mVp-p(lout=5A)                                                              |
| Line regulation                                                              | +/-1%                                                                           |
| Load regulation                                                              | +/-1%(static), +/-2%(dynamic)                                                   |
| Hold up time                                                                 | >20ms @400Vac                                                                   |
| Over current, Over voltage,<br>Over temperature,<br>Short circuit protection | Yes                                                                             |
| Signaling                                                                    | Power OK LED                                                                    |
| Insulation (P to S)                                                          | 4 KV AC                                                                         |
| Operating temperature range                                                  | -25 °C to 70 °C<br>(>60°C Derating 2.5%/K)                                      |
| Operation humidity range                                                     | < 95%                                                                           |
| Operation altitude                                                           | 2000M                                                                           |
| Dimensions (D × W × H)                                                       | 125 X 40 X 130mm                                                                |
| Approvals                                                                    | cURus,CE,CB,UL508,<br>EN60950,EN62368                                           |
| MTBF(40degC)                                                                 | >480,000hrs                                                                     |
| Weight                                                                       | 1.0kg                                                                           |